

Connector Blocks



Description

- > Terminal blocks are brass with serrated bores to suit both stranded copper and solid aluminium conductors.
- > Two M8 grub screws are provided for each cable way.
- > Housings are black phenolic with knock-outs at each cable entry.
- > Cover screw is wire sealable.
- > Length 60mm, Width 51mm, Depth 45mm.
- > Self adhesive earth indicator label included for optional use.

Connector Blocks

BICON

Single Pole

Double Pole



Description

- > A two level design with a separate removeable compartment for the neutral terminal block, providing easy access for cabling both phase and neutral terminal block through knock-outs.
- > Housings are black phenolic with knock-outs at each cable entry.
- > The phase terminal block is colour coded red.
- > Terminal blocks and grub screws are tin plated.
- > Cover screws are wire sealable.
- > Length 54mm, Width 87mm, Depth 53mm.

Ref: CBLOCK/03/10



UNIT 14 PARK COURT | SULLIVANS WAY | ST. HELENS | WA9 5GZ | UK

Tel: +44 (0)1744 762 929 | Fax: +44 (0)1744 762 930
Email: sales@etechcomponents.com | Web: www.e-tech-components.co.uk



Connector Blocks

Block Details

Single Pole Connector Blocks 100A.



| Design No. | Maximum conductor size | | No. of ways |
|------------|---|------------------------|-------------|
| | Stranded copper or aluminium mm ² | SAC mm ² | |
| G72273-60 | 35 | 50 | 5 |

Double Pole Connector Blocks



| Design No. | Maximum conductor size. | No. of ways |
|------------|---|-------------|
| | Per pole Stranded copper mm ² | |
| G70098-02 | 16 (2 ways) 25 (3 ways) | 5 |