



Afumex Two Bolt Cleat (LSOH) 374 series

- Suitable for use with cable diameters 50 to 94mm.
- Manufactured from LSOH Polymer.
- Designed for use with Afumex LSOH and Saffire OHLS cables.
- Low Smoke and Zero Halogen.
- Sunlight (UV) and weather resistant.
- Two-piece, two fixing design.
- Can be double stacked on common fixings.
- Operating temperature -40°C to +60°C.
- Tested in accordance with BS EN 50368.
- LUL APR Product ID 1958.

SINGLE WAY CLEATS

Technical Data

Afumex SAFFIRE^{OHLS}

| Cable and Cleat Selection | | | Cleat Details | | | | Weight (g) |
|---------------------------|----------------|-----|---------------|-----------------|----|-----|------------|
| Design Number | Cable Diameter | | B Max | Dimensions (mm) | | | |
| | Min | Max | | C | D | E | |
| 374LSF01 | 50 | 58 | 89 | 102 | 45 | 80 | 174 |
| 374LSF02 | 56 | 64 | 93 | 102 | 45 | 80 | 158 |
| 374LSF03 | 62 | 70 | 98 | 114 | 45 | 92 | 174 |
| 374LSF04 | 68 | 76 | 104 | 114 | 50 | 92 | 210 |
| 374LSF05 | 74 | 82 | 110 | 126 | 50 | 104 | 254 |
| 374LSF06 | 80 | 88 | 118 | 126 | 50 | 104 | 264 |
| 374LSF07 | 86 | 94 | 121 | 136 | 60 | 114 | 326 |

Method of Fixing

In all applications the cleat should be mounted on suitable M10 fixings. There is no need for any channel adaptor when mounting directly on to 'C' section channel.



Performance Data

| | |
|--------------------------|--------------------|
| Test Standard | EN 50368:2003 |
| Type | 6.1.2 Non-Metallic |
| Impact Resistance | 6.2.5 V. Heavy |
| Lateral Load | 1.22 -> 3.485 kN |
| Axial Load | 82 -> 110 N |
| Needle Flame | >120 secs |

* Technical Information subject to change without notice

