


Cleats & Cable Fixings

Single Way & Trefoil Cleats

Multicleat System - Installed Dimensions & Weights

MULTICLEAT DIMENSIONS (MAXIMUM CABLE SIZE) (mm)



Style		Overall Height B				Overall Width C+				Bolt Centres D		Strap Length	
		2 Bolt, Types: AB, AD, AK, CB, CD, JB		1 Bolt Type: PF		2 Bolt		1 Bolt, Type: PF		2 Bolt			
Standard Duty	Heavy Duty	Trefoil Cable	Single Cable	Trefoil Cable	Single Cable	Types AB, AD, AK, CB, CD	Type: JB	Trefoil Cable	Single Cable	Types: AB, AD, AK, CB, CD	Type: JB	Standard Duty	Heavy Duty
01	51	95	92	99	96	126	110	76	76	100	84	555	785
02	52	110	113	113	116	126	110	82	85	100	84	620	895
03	53	121	118	121	118	122	122	102	102	96	96	700	1025
04	54	135	138	135	138	122	122	108	110	96	96	785	1135
05	55	146	-	147	-	132	132	120	-	106	106	855	1245
06	56	160	-	161	-	134	134	134	-	106	106	940	1370
07	57	172	-	173	-	176	152	146	-	150	126	1025	1505
08	58	186	-	187	-	176	160	160	-	150	126	1100	1620
09	59	-	148	-	-	122	122	-	120	96	96	855	1245
-	29	-	136	-	-	174	-	-	-	148	-	-	1245
-	39	238	-	-	-	268	-	-	-	242	-	-	2270

+ C is the greater of the dimensions across the cleat base or the cables.

WEIGHTS OF MULTICLEATS WITH LISTED BASES AND MULTISTRAPS (g)

Style	Standard Duty					Heavy Duty					
	Aluminium Base 378AB 378AD 378AK	Stainless Steel Cast Base 378JB	Stainless Steel Cast Base 378PF	Cast Iron Base 378CB 378CD	Multistrap 377AB	Style	Aluminium Base 378AB 378AD 378AK	Stainless Steel Cast Base 378JB	Stainless Steel Cast Base 378PF	Cast Iron Base 378CB 378CD	Multistrap 377AB
01	450	620	435	990	140	51	520	690	505	1060	210
02	470	640	455	1010	160	52	550	720	535	1090	240
03	520	720	550	1150	170	53	600	800	630	1220	250
04	530	730	560	1160	180	54	630	830	660	1250	280
05	620	810	605	1420	190	55	720	910	705	1520	290
06	630	820	615	1430	200	56	740	930	725	1530	310
07	690	950	720	1550	220	57	800	1050	820	1660	320
08	710	960	730	1560	230	58	840	1090	860	1690	360
09	540	740	570	1170	-	59	640	840	670	1270	-
-	-	-	-	-	-	29	830	-	-	-	-
-	-	-	-	-	-	39	1500	-	-	-	620

METHOD OF FIXING

In all applications the Multicleat bases should be mounted on either one or two M10 fixings as appropriate. It is essential that they are secured to supports capable of withstanding the prospective short circuit forces.