

Northbrook, Illinois • (847) 272-8800
 Melville, New York • (631) 271-6200
 Santa Clara, California • (408) 985-2400
 Research Triangle Park,
 North Carolina • (919) 549-1400
 Camas, Washington • (360) 817-5500



PIRELLI CABLES LTD
 MR T DOUBLEDAY
 COMPONENTS UNIT
 PO BOX 4, HALL LN
 MERSEYSIDE, PRESCOT
 L34 5UR ENGLAND UNITED KINGDOM

Your most recent Certification is shown below. You may also view this information, or a portion of this information (depending on the product category), on UL's Online Certifications Directory at www.ul.com/database. Please review the text and contact the Conformity Assessment Services staff member who handled your project if revisions are required. For instructions on placing an order for this information in a 3 x 5-inch format, you may refer to the enclosed order form for UL Card Service.

PJOX
Metal-clad Cable Connectors, Type MC

July 25, 2002

PIRELLI CABLES LTD
COMPONENTS UNIT PO BOX 4, HALL LN MERSEYSIDE,
PRESCOT, L34 5UR ENGLAND UNITED KINGDOM

E122761

Connectors for use with Metal-Clad Cable (Type MC) with continuous corrugated aluminum or interlocked aluminum armor.

Connectors for use with Metal-Clad Cable (Type MC) with continuous corrugated aluminum or interlocked aluminum armor.

**Cable Diam Range
 Over Armor In.**

Cat. No.	Trade Size In.	Min	Max
416MA02+, 416MC02+	1/2	0.460	0.500
416MA03+, 416MC03+	3/4	0.485	0.680
416MA04+, 416MC04+	1	0.650	0.890
416MA05+, 416MC05+	1-1/4	0.865	1.140
416MA06+, 416MC06+	1-1/2	1.100	1.350
416MA07+, 416MC07+	2	1.320	1.540
416MA08+, 416MC08+	2-1/2	1.510	2.080
416MA09+, 416MC09+	3	2.070	2.700
416MA10+, 416MC10+	3-1/2	2.900	3.350
416RA02+, 416RC02+	1/2	0.460	0.500
416RA04+, 416RC04+	1	0.650	0.890
416RA05+, 416RC05+	1-1/4	0.865	1.140
416RA06+, 416RC06+	1-1/2	1.100	1.350
416RA07+, 416RC07+	2	1.320	1.540
416RA08+, 416RC08+	2-1/2	1.510	2.080
416RA09+, 416RC09+	3	2.070	2.700
416RA10+, 416RC10+	3-1/2	2.900	3.350
416UL-01+	1/2	0.54	1.00
416UL-02+	1/2	0.54	1.00

Underwriters Laboratories Inc.®

Cat. No.	Trade Size In.	Cable Diam Range Over Armor In.	
		Min	Max
416UL-03+	3/4	0.89	1.23
416UL-04+	1	1.23	1.44
416UL-05+	1-1/4	1.43	1.84
416UL-06+	1-1/2	1.84	2.21
416UL-07+	2	2.14	2.76
416UL-08+	2-1/2	2.69	3.04
416UL-09+	3	2.97	3.62
416UL-10+	3-1/2	3.55	4.24

+Indicates rain tight.

LOOK FOR LISTING MARK ON PRODUCT